



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User Manual
--------------------	-------------

Physical

Cable length	4 ft (1.22 m)
Color	Black
Maximum Depth	13.98 in (35.5 cm)
Height	6.30 in (16 cm)
Net Weight	13.45 lb(US) (6.1 kg)
Maximum Width	4.72 in (12 cm)

Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Plug standard	IEC 60320 C14
Efficiency at full load	140...300 V
Nominal Input Voltage	230 V

Output

Rated power in W	520 W
Max Configurable Power (Watts)	520 W
Output Frequency (sync to mains)	50/60 Hz +/- 1 Hz sync to mains
Topology	Standby
Waveform Type	Stepped approximation to a sinewave
Nb of power socket outlets	2 universal 2 IEC 60320 C13
Output voltage	230 V

Conformance

Product certifications	CE
Standards	EN/IEC 62040-1 EN/IEC 62040-2 CE
Equipment protection policy	Lifetime : 50000 Euros

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 ft
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Storage altitude	0...3000 ft (0.00...914.40 m)
Acoustic level	40 dBA
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	8 h
Liquid Electrolyte Value	0

Communications & Management

Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm

Surge Protection and Filtering

Surge energy rating	273 J
Data Line Protection	RJ45 10/100/1000 Base-T Ethernet protection

Ordering and shipping details

Package weight(Lbs)	14.55 lb(US) (6.6 kg)
---------------------	-----------------------

Packing Units

Package 1 Height	9.84 in (25 cm)
Package 1 width	7.76 in (19.7 cm)
Package 1 Length	16.93 in (43 cm)
SCC14	10731304410703

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------