



3MP **PIXEL** **HD**
4G PT Dome camera





Feature



- * 4G PT Dome camera 4G
- * Resolution 3MP
- * Sensor 1/3" CMOS Sensor
- * Shutter Shutter adaptation
- * Lens 4mm
- * IR Distance IR 20-30m, spotlight 15m
- * Video Compression H.265 / H.264
- * Frame Rate Max 15fps
- * Interface Micro SD Card (max 256G)
- * Cloud Storage Support
- * Power Adapter DC 12V 1A

Specification

Model		HW-33MPT302-4G	
Resolution	3MP		
Sensor	1/3" CMOS Sensor		
Shutter	Shutter adaptation		
Lens	4mm		
Rotation Angle	Pan: 0~263 0.1~20/S Tilt :0~105 0.1~20/S		
Day-night	mode Infrared filter		
DNR	3D digital noise reduction		
Dynamic Range	Digital WDR		
IR Distance	IR 20-30m, spotlight 15m (depends on environment)		
Compression Standard			
Video Compression	H.265 / H.264		
Video Compression	HD / SD		
Audio Coding Format	AAC / G711A		
Image			
Resolution	Main stream: 2304 *1296 Sub stream: 640x360		
Frame Rate	Max 15fps		
Image reversal	Support mirror and flip reversal		
Privacy Masking	Support		
Alarm Function			
Intelligent Alarm	Motion detection		
Alarm Notification	Alarm notification push		
Storage			
Interface	Micro SD Card (max 256G)		
Cloud Storage	Support		
Wireless Spec			
Wireless Standard	4G: LTE-TDD/LTE FDD; WIFI:802.11bgn		
Wireless Frequency Band	LTE-FDD: B1/B3/B5/B8 LTE-TDD: B40 WIFI: 2400MHz-2483.5MHZ		
General Specs			
Working Temperature	-20℃-50℃, Working Humidity: <95%		
Working Humidity	<95% <95% (no condensation)		
Power Adapter	DC 12V 1A		